



ALBURY MOTORS (77) PTY. LTD.  
480 Townsend St., Albury. 2640  
Authorised Mercedes Benz Sales and Service  
Telephone 21 2188



**PEUGEOT**  
*'take another look'*



<b>504 Specifications</b>	<b>Automatique Sedan</b>	<b>GL Sedan</b>	<b>Superluxe Estate</b>	<b>Family Estate</b>
	4 cylinder alloy crossflow-head with hemispherical combustion chambers, wet sleeves, 5 bearing crankshaft inclined 45°, electro thermo magnetic fan			
ENGINE Type	1971 cm <sup>3</sup>	1971 cm <sup>3</sup>	1971 cm <sup>3</sup>	1971 cm <sup>3</sup>
Capacity	88 mm x 81 mm	88 mm x 81 mm	88 mm x 81 mm	88 mm x 81 mm
Bore & Stroke	8.35:1	8.35:1	8.35:1	8.35:1
Compression Ratio	89.23 @ 5250 r.p.m.	89.23 @ 5250 r.p.m.	89.23 @ 5250 r.p.m.	89.23 @ 5250 r.p.m.
Maximum Power (a) bhp DIN	66.25 @ 5250 r.p.m.	66.25 @ 5250 r.p.m.	66.25 @ 5250 r.p.m.	66.25 @ 5250 r.p.m.
DIN kW	3-speed Borg Warner torque tube connection and hypoid rear axle	4-speed synchromesh gearbox, torque tube connection and hypoid rear axle.	4-speed synchromesh gearbox, torque tube connection and hypoid rear axle.	4-speed synchromesh gearbox; torque tube connection and hypoid rear axle.
TRANSMISSION Gearbox	29.75	29.75	28.00	28.00
Km/h per 1000 rpm in top gear	Independent with 2-coil springs, telescopic shock absorbers, anti-roll bar			
Suspension front	Independent with 2-coil springs trailing A-frames telescopic shock absorbers and anti-roll bar		4-coil springs, stabilising bar, live rear axle, anti-roll bar telescopic shock absorbers	
Suspension rear	Rack and pinion, two section safety steering column, anti-theft lock, 4.5 turns lock to lock			
Steering	5J14	5J14	5J14	5J14
Wheels	175 x 355	175 x 355	185 x 355	185 x 355
Tyres	Dual Power assisted with variable pressure distribution through load sensitive limiting device. Pad wear warning system on front and rear brakes. Brake fluid loss warning system. Hand brake operates on rear wheels.			
BRAKES	Solid discs 273 mm diameter	Solid discs 273 mm diameter	Solid discs 273 mm diameter	Solid discs 273 mm diameter
Front	Solid discs 273 mm diameter	Solid discs 273 mm diameter	Drum 280 mm diameter	Drum 280 mm diameter
Rear	56 litres	56 litres	60 litres	60 litres
Fuel Capacity	4 litres	4 litres	4 litres	4 litres
Engine Oil Capacity	5 litres	1.15 litres	1.15 litres	1.15 litres
Transmission Capacity Gearbox	1.20 litres	1.20 litres	1.60 litres	1.60 litres
Differential	7.8 litres	7.8 litres	7.8 litres	7.8 litres
Coolant Capacity	12 volt. Alternator 40 amps. Battery 46 amp/hr			
Electrical Equipment	4.49 metres	4.49 metres	4.80 metres	8.40 metres
Length	1.69 metres	1.69 metres	1.69 metres	1.69 metres
Width	2.74 metres	2.74 metres	2.90 metres	2.90 metres
Wheelbase	1230 kg	1230 kg	1275 kg	1330 kg
Kerb Weight	0.55 m <sup>3</sup> (19.40 cu ft)	0.55 m <sup>3</sup> (19.40 cu ft)	1.10 m <sup>3</sup> (39.2 cu ft) back seat up 1.80 m <sup>3</sup> (64.3 cu ft) back seat folded down	0.33 m <sup>3</sup> (11.65 cu ft) back seat up 0.65 m <sup>3</sup> (22.95 cu ft) back seat folded down
Luggage	615 kg	615 kg	665 kg	665 kg
Towing Capacity	1300 kg	1300 kg	1500 kg	1500 kg
– without trailer brakes				
– with trailer brakes				

The description and characteristics data of models are given only by way of indication and are subject to alteration without prior notice. This may apply to both the mechanical specifications and body parts of our models.  
Renault (Australia) Pty Ltd.  
February 1977.

(a) The output given in DIN/hp or kW is effectively available at the clutch for driving the vehicle. Any other power consumption has already been deducted.